


1mm	Socket	Double Row - Barrel Contact	Straight	Thru Hole
-----	--------	-----------------------------	----------	-----------

1mm Center Double Row Socket - round barrel contact



Base Part Number	A		B		C		D		E		Plating Options	Number of Positions
	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch		
6451	4.57	0.180	3.68	0.145	0.89	0.035	2.79	0.110			G1	4-80
6452	5.59	0.220	3.68	0.145	19.05	0.750	2.79	0.110			G1	4-80
6454	6.35	0.250	3.68	0.145	2.67	0.105	2.79	0.110			G1	4-80
6453	7.62	0.300	3.68	0.145	3.94	0.155	2.79	0.110			G1	4-80

Technical Notes	
Contact Material:	Contact: Stamped - BeCu
Insulation Material:	Glass Filled Nylon 46 - UL 94V-0 rated - Black (std)
Heat Deflection:	260°C @ 264 PSI per ASTM D648
Insulation Resistance:	5000 MegOhm @ 500VDC
Current Rating:	1 amp continuous @ 100 VDC/contact
Max Processing Temp:	250°C for 60 seconds
Insertion Force:	75 grams (2.6 oz) (typical initial w/ .012 inch square pin)
Extraction Force:	49 grams (1.7 oz) (typical initial w/ .012 inch square pin)
Plastic:	High Temperature Compatible

COMM CON CONNECTORS INC.

1848 Evergreen Street, Duarte, Ca 91010 · (626) 301-4200 · fax (626) 301-4212 · e-mail:

info@commcon.com